



ANCHOR BOLT & ISOLATOR MOUNTING LOCATIONS

ANTI-VIBRATION MOUNT TABULATE DATA

SELECO ISOLATOR MOUNTS (NEW) - START SN EB23000593				
MODEL #	G1	G2	G3	G4
250 & 250 W/CR	BB100-60SH	BB100-70SH	BB100-70SH	BB100-70SH
VIBROSTOP ISOLATOR MOUNTS (OLD) - PHASED OUT				
250 & 250 W/CR	ALL BLACK RUBBER AA200/N			

SOLECO ISOLATOR MOUNTS TO USE ARE RUBBER AT LOCATIONS WITH COLORS AS NOTED: 60 = RED, 70 = GRAY

MODEL #	USER WATER IN Uin (NPTF)	USER WATER OUT Uout(NPTF)	RECOVERY WATER IN Sin (NPTF)	RECOVERY WATER OUT Sout(NPTF)	WEIGHT (Lb/Kg)	OPERATING WEIGHT (Lb/Kg)
250	1-1/2"	1-1/2"	1-1/2"	1-1/2"	2044/927	2055/932
250 W/CR	1-1/2"	1-1/2"	1-1/2"	1-1/2"	2050/930	2070/939

- NOTES:
 1) ALL DIMENSIONS SHOWN ARE IN INCHES (MILLIMETERS).
 2) LYNCE RESERVES THE RIGHT TO MODIFY DIMENSIONS WITHOUT PRIOR NOTICE.
 3) ONLY FOR RECOVERY VERSION.
 4) FOR ANTI-VIBRATION ISOLATOR MOUNTS, SEE TABULATE DATA.

Lynce Blauvelt, NY
Fort Worth, TX

AEGIS A 250
DIMENSIONAL/CLEARANCE DRAWING

DWN.BY <u>K.S.</u> DATE <u>092120</u>	AP-L-1059	REV. G
SCALE <u>NTS</u>		
REV.BY <u>K.S.</u> DATE <u>120924</u>		