



ANCHOR BOLT LOCATIONS & ISOLATOR MOUNTING

MODEL #	USER WATER IN Uin (NPTF)	USER WATER OUT Uout(NPTF)	RECOVERY WATER IN Sin (NPTF)	RECOVERY WATER OUT Sout(NPTF)	WEIGHT (Lb/Kg)	OPERATING WEIGHT (Lb/Kg)
250	1-1/2"	1-1/2"	1-1/2"	1-1/2"	2044/927	2055/932
250 W/CR	1-1/2"	1-1/2"	1-1/2"	1-1/2"	2050/930	2070/939

- NOTES:  
 1) ALL DIMENSIONS SHOWN ARE IN INCHES (MILLIMETERS).  
 2) LYNCS RESERVES THE RIGHT TO MODIFY DIMENSIONS WITHOUT PRIOR NOTICE.  
 3) ONLY FOR RECOVERY VERSION.  
 4) ANTI-VIBRATION ISOLATOR MOUNTS TO USE ARE ALL BLACK RUBBER #AA200/N.



AEGIS A 250  
DIMENSIONAL/CLEARANCE DRAWING

DWN.BY K.S. DATE 092120  
 SCALE NTS  
 REV.BY K.S. DATE 101723

AP-L-1059

REV.  
F